

## FibRSol – FTTH Drop Cable

Model: FS-Drop Wire-With Glass Yarn

### Highlights:

- ✓ G.657A
- ✓ FRP
- ✓ Steel
- ✓ LSZH
- ✓ Glass Yarn



**FS-Drop Wire-With Glass Yarn**

### Application:

Design for FTTH interconnection solution: Used in indoor cabling, especially used under carpet.

### Features:

- ✓ Special low-bend-sensitivity fiber provides high bandwidth and excellent communication transmission property.
- ✓ One parallel strength members with glass yarn ensure good mechanical characteristic to protect the fiber, especially has exceptional performance on crush and torsion, both FRP and Steel wire strength member are available:
  - Novel flute design, easily strip and splice, simplify the installation and maintenance,
  - 2 fiber is available in the optical fiber unit.
  - Flame retardant low smoke zero halogen outer jacket
  - RoHS compliance

## Cable Parameter:

<b>Fiber Type:</b>	G.657A
<b>Fiber Count:</b>	1
<b>Strength Member:</b>	FRP Glass Yarn
<b>Dimension:</b>	3.0±0.1 x2.0.1 mm
<b>Material:</b>	LSZH
<b>Color:</b>	Black or other coloured as customer's request

## Mechanical & Environmental Characteristics:

Item	Unite	Specification
Tensile (Long Term):	N	60
Tensile (short Term):	N	100
Crush (Long Term):	N/10cm	500
Crush (Short Term):	N/10cm	1000
Min. Bend Radius (Static):	mm	10
Min. Bend Radius (Dynamic):	mm	25
Work Temperature:	°C	-40~+70
Operation Temperature:	°C	-20~+60
Storage Temperature:	°C	-30~+70



## Ordering Information:

Model	Description
FS-DROP WIRE	1F, G.657A, FRP Glass Yarn, LSZH